



EX STOCK • EX STOCK

Seamless Austenitic Stainless Steel Tubes for High-Temperature Service Grade TP 304H, TP 347H, TP 321H

- ▶ We have extended our stock programme for you:
seamless austenitic stainless steel pipes in TP 304H and TP347H
- ▶ Main use of the high alloy material is for boiler tubes
in power stations and refineries
- ▶ Special properties:
 - high creep rupture strength above 500°C
 - excellent resistance to high-temperature corrosion
 - excellent processing characteristics

Chemical composition (heat analysis in %)

	C	Si	Mn	P	S	Cr	Ni	others
TP 304H	0,04-0,08	0,75	2,0	0,035	0,015	17,0-19,0	8,0-11,0	–
TP 347H	0,04-0,08	0,75	2,0	0,035	0,015	17,0-19,0	9,0-12,0	Nb10xC up to 1,00
TP 321H	0,04-0,08	0,75	2,0	0,035	0,015	17,0-19,0	9,0-12,0	Ti 5xC up to 0,80

Mechanical properties at room temperature

	tensile strength N/mm ²	yield strength		elongation at fract. longit. (L ₀ =5d ₀) %	notch impact energy (ISO-V) longitud. J
		0,2 % N/mm ²	1 % N/mm ²		
TP 304H	515-700	min.195	min.230	min.40	min.100
TP 347H	515-740	min.205	min.240	min.35	min.100
TP 321H	480-730	min.180	min.215	min.35	min.100

Seamless austenitic stainless steel tubes and pipes for High-Temperature Service (available from stock)

OD mm	WT mm	kg/m	NPS	TP304/ TP304H	TP321/ TP321H	TP347/ TP347H
13,72 x 2,24	0,64		1/4" SCH 40S		x	
21,34 x 2,11	1,02		1/2" SCH 10S		x	
21,34 x 2,77	1,29		1/2" SCH 40S	x	x	x
21,34 x 3,73	1,64		1/2" SCH 80S	x	x	x
21,34 x 4,78	1,98		1/2" SCH 160		x	
21,34 x 7,47	2,59		1/2" SCH XXS		x	
26,67 x 2,11	1,30		3/4" SCH 10S		x	
26,67 x 2,87	1,71		3/4" SCH 40S	x	x	x
26,67 x 3,91	2,23		3/4" SCH 80S	x	x	x
26,67 x 5,54	2,93		3/4" SCH 160		x	
26,67 x 7,82	3,69		3/4" SCH XXS		x	
33,40 x 2,77	2,12		1" SCH 10S		x	
33,40 x 3,38	2,54		1" SCH 40S	x	x	x
33,40 x 4,55	3,29		1" SCH 80S	x	x	x
33,40 x 6,35	4,30		1" SCH 160		x	
33,40 x 9,09	5,53		1" SCH XXS		x	
42,16 x 2,77	2,73		1 1/4" SCH 10S		x	
42,16 x 3,56	3,44		1 1/4" SCH 40S	x	x	x
42,16 x 4,85	4,53		1 1/4" SCH 80S		x	
42,16 x 6,35	5,69		1 1/4" SCH 160		x	
42,16 x 9,70	7,88		1 1/4" SCH XXS		x	
48,26 x 2,77	3,16		1 1/2" SCH 10S		x	
48,26 x 3,68	4,11		1 1/2" SCH 40S	x	x	x
48,26 x 5,08	5,49		1 1/2" SCH 80S	x	x	x
48,26 x 7,14	7,35		1 1/2" SCH 160		x	
48,26 x 10,16	9,69		1 1/2" SCH XXS		x	
60,33 x 2,77	3,99		2" SCH 10S		x	
60,33 x 3,91	5,52		2" SCH 40S	x	x	x
60,33 x 5,54	7,60		2" SCH 80S	x	x	x
60,33 x 8,74	11,29		2" SCH 160		x	
60,33 x 11,07	13,65		2" SCH XXS		x	
73,03 x 3,05	5,34		2 1/2" SCH 10S		x	
73,03 x 5,16	8,77		2 1/2" SCH 40S	x	x	x
73,03 x 7,01	11,59		2 1/2" SCH 80S		x	
73,03 x 9,53	15,15		2 1/2" SCH 160		x	
73,03 x 14,02	20,72		2 1/2" SCH XXS		x	
88,90 x 3,05	6,56		3" SCH 10S		x	
88,90 x 5,49	11,47		3" SCH 40S	x	x	x
88,90 x 7,62	15,51		3" SCH 80S	x	x	x
88,90 x 11,13	21,67		3" SCH 160		x	
88,90 x 15,24	28,11		3" SCH XXS		x	

OD mm	WT mm	kg/m	NPS	TP304/ TP304H	TP321/ TP321H	TP347/ TP347H
101,60 x 3,05	7,53		3 1/2" SCH 10S		x	
101,60 x 5,74	13,78		3 1/2" SCH 40S		x	
101,60 x 8,08	18,92		3 1/2" SCH 80S		x	
114,30 x 3,05	8,50		4" SCH 10S		x	
114,30 x 6,02	16,32		4" SCH 40S	x	x	x
114,30 x 8,56	22,66		4" SCH 80S	x	x	x
114,30 x 11,13	28,75		4" SCH 120		x	
114,30 x 13,49	34,05		4" SCH 160		x	
114,30 x 17,12	41,66		4" SCH XXS		x	
141,30 x 3,40	11,74		5" SCH 10S		x	
141,30 x 6,55	22,10		5" SCH 40S	x	x	x
141,30 x 9,53	31,44		5" SCH 80S		x	
141,30 x 15,88	49,87		5" SCH 160		x	
168,30 x 3,40	14,04		6" SCH 10S		x	
168,30 x 7,11	28,70		6" SCH 40S	x	x	x
168,30 x 10,97	43,22		6" SCH 80S	x	x	x
168,30 x 14,27	55,04		6" SCH 120		x	
168,30 x 18,26	68,60		6" SCH 160		x	
168,30 x 21,95	80,44		6" SCH XXS		x	
219,10 x 3,76	20,27		8" SCH 10S		x	
219,10 x 8,18	43,20		8" SCH 40S	x	x	x
219,10 x 10,31	53,90		8" SCH 60		x	
219,10 x 12,70	65,64		8" SCH 80S	x	x	x
219,10 x 18,26	91,83		8" SCH 120		x	
219,10 x 23,01	112,98		8" SCH 160		x	
273,00 x 9,27	61,22		10" SCH 40S		x	
273,00 x 12,70	82,78		10" SCH 80S		x	
273,00 x 21,44	135,05		10" SCH 120		x	
273,00 x 28,58	174,92		10" SCH 160		x	
323,90 x 9,52	74,94		12" SCH 40S		x	
323,90 x 12,70	98,96		12" SCH 80S		x	
323,90 x 17,48	134,12		12" SCH 80		x	
323,90 x 21,44	162,38		12" SCH 100		x	
323,90 x 33,32	242,44		12" SCH 160		x	
355,60 x 9,52	82,50		14" SCH 40S		x	
355,60 x 12,70	109,04		14" SCH 80S		x	
355,60 x 19,05	160,54		14" SCH 80		x	
355,60 x 23,83	197,97		14" SCH 100		x	
355,60 x 27,79	228,11		14" SCH 120		x	
355,60 x 35,71	286,04		14" SCH 160		x	
406,40 x 12,70	125,20		16" SCH 80S		x	
406,40 x 21,44	206,67		16" SCH 80		x	

Stock standard:

ASTM/ASME A/SA 312/376, EN10216-5, TC1, IC-Test acc. to ASTM A262 Practice E, NACE MR0175; mill inspection certificate EN DIN 10204/3.1

Grades:

TP 304/304H (1.4301, 1.4948); TP 321/321H (1.4541, 1.4878); TP 347/347H (1.4550, 1.4912)

Please ask us also for TP316 with C \geq 0,04 %.

Supplementary requirement (upon request):

TP 347/347H with stabilizing heat treatment at 900°C for 30 minutes.

Stahlkontor Hahn - Your Master Distributor

Stahlkontor Hahn
Division of ThyssenKrupp MetalServ GmbH

Borsigstraße 2
40880 Ratingen, Germany

Tel.: +49-2102-402.210
Fax: +49-2102-402.262



SKH02/2011

dirk.waltemode@s-k-h.com · www.s-k-h.com

EX STOCK · EX STOCK · EX STOCK